

AFTERMARKET AUTO PARTS ALLIANCE, INC
2706 TREBLE CREEK, SUITE 100
SAN ANTONIO, TX, 78258

PRODUCT: AV 7658 ROCKER PANEL PROTECTOR BLACK**Section 01: Chemical product and company identification**

Product name..... AV 7658 ROCKER PANEL PROTECTOR BLACK
Manufactured for..... Aftermarket Auto Parts Alliance, Inc
2706 Treble Creek, Suite 100
San Antonio, TX 78258
24 hour emergency number:..... IN CANADA CALL CANUTEC (613) 996-6666-IN THE UNITED STATES CALL
CHEMTREC (800) 424-9300.
Material use..... Paints. This product should not be used for any other purpose other than the ones
described in this section.
Chemical family..... Mixture.
Preparation date..... March 12, 2015.
Hazard rate
NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.
HMIS..... H: 2 F: 4 R: 0.

Section 02: Hazards identification

Signal Word..... DANGER.
Hazard Classification..... Flammable Aerosol 1. Gas under pressure: Compressed Gas. Aspiration Toxicity 1. Skin Irritant 2. STOT SE 3. Carcinogen 2. Reproductive 2. STOT RE 2.
Hazard Description..... H222 Extremely flammable aerosol . H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H351 This product contains ingredients that are suspected of causing cancer. H361 This product contains ingredients that are suspected of damaging fertility or the unborn child. H373 May cause damage to the liver and kidneys through prolonged or repeated contact.
Precautionary Statements..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition sources. P251 Do not pierce or burn container, even after use. P260 Do not breathe the mist, vapours, or spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.
Response P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P302 + P352 - If on skin: wash with plenty of water. . P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P308 + P313 If exposed or concerned, get medical advice/attention. P312 Call a POISON CENTER/doctor if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - Consult with a doctor or poison control centre if skin is itchy or a skin rash develops or you feel unwell. P332 + P313 - If skin irritation occurs get medical attention or advice. P362 + P364 - Take off contaminated clothing and wash before reuse. P331 Do NOT induce vomiting.
Storage..... P403 + P233 Store in a well ventilated area. Keep container tightly closed. P405 Store locked up. P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50°C / 122°F.
Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Wt. %
ACETIC ACID, TERT-BUTYL ESTER	540-88-5	15-40
TOLUENE	108-88-3	15-40
CALCIUM CARBONATE	1317-65-3	7-13
PROPANE	74-98-6	7-13
SBR (STYRENE BUTADIENE RUBBER)	9003-55-8	5-10

PRODUCT: AV 7658 ROCKER PANEL PROTECTOR BLACK**Section 03: COMPOSITION/INFORMATION ON INGREDIENTS**

ISOBUTANE	75-28-5	5-10
SOLVENT NAPHTHA, HEAVY ALIPHATIC	64742-96-7	1-5
BENTONE	68953-58-2	0.1-1.0
CARBON BLACK	1333-86-4	0.1-1.0
CRYSTALLINE SILICA	14808-60-7	0.1-1.0

Section 04: First aid measures

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	If ingestion is suspected, contact physician or poison control center immediately. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Additional information.....	Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

Section 05: Fire fighting measures

Extinguishing media.....	Foam, "alcohol" foam, co2, dry chemical, water fog.
Hazardous combustion products.....	Oxides of carbon (CO, CO2).
Special fire fighting procedures.....	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Heat will cause pressure buildup and may cause explosive rupture.

Section 06: Accidental release measures

Leak/spill.....	Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%).
-----------------	---

Section 07: Handling and storage

Handling procedures.....	Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from heat, sparks, and open flame.
Storage needs.....	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

Section 08: Exposure controls / personal protection

Ingredients	TWA	ACGIH TLV STEL	PEL	OSHA PEL		NIOSH REL
				PEL	STEL	
ACETIC ACID, TERT-BUTYL ESTER	200 ppm	Not established	200 ppm	Not established		200 ppm
TOLUENE	20 ppm	Not established	200 ppm	500 ppm 10 minutes		100 ppm / STEL 150 ppm
CALCIUM CARBONATE	No data No data	No data	5 mg/m3	No data		5 mg/m3

PRODUCT: AV 7658 ROCKER PANEL PROTECTOR BLACK**Section 08: Exposure controls / personal protection**

Ingredients	ACGIH TLV		OSHA PEL		NIOSH REL
	TWA	STEL	PEL	STEL	
PROPANE	1,000 ppm No data	Not established	1,000 ppm	Not established	1,000 ppm
SBR (STYRENE BUTADIENE RUBBER)	Not established	Not established	Not established	Not established	Not established
ISOBUTANE	Not established No data	Not established	Not established	Not established	800 ppm
SOLVENT NAPHTHA, HEAVY ALIPHATIC	No data	No data	No data	No data	No data
BENTONE	No data	No data	No data	No data	No data
CARBON BLACK	3.5 mg/m3 No data	Not established	3.5 mg/m3	Not established	3.5 mg/m3
CRYSTALLINE SILICA	0.025 mg/m3 No data	No data	No data	No data	0.05 mg/m3

Protective equipment

Eye/type.....	Liquid chemical goggles.
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.
Gloves/ type.....	Chemical resistant gloves.
Clothing/type.....	Wear adequate protective clothes.
Footwear/type.....	Safety boots per local regulations.
Other/type.....	Emergency showers and eye wash stations should be available.
Ventilation requirements.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. .

Exposure limits

Section 09: Physical and chemical properties

Physical state.....	Aerosol.
Colour.....	Black.
Odour.....	Solvent odour.
Odour threshold (ppm).....	No data.
Vapour pressure (mm Hg).....	60-80 psig @ 21°C .
Vapour density (air=1).....	>1.
pH.....	Not applicable.
Specific gravity.....	Liquid: 1.00 (8.35 lb/usg); Aerosol: 0.93 (7.76 lb/usg) .
Freezing point (deg C).....	No data.
Solubility.....	Insoluble.
Boiling point (deg C).....	97°C.
Evaporation rate.....	Greater than n-butyl acetate.
Flash point (deg C), method.....	-4.0°C Closed Cup.
Auto ignition temperature (deg C).....	450°C.
Upper flammable limit (% vol).....	7.
Lower flammable limit (% vol).....	1.2.
Coefficient of water/oil distribution.....	No data.
VOC.....	2.38 lb/usg - 285 g/L.
Viscosity.....	6920 cps Spindle #4.

Section 10: Stability and reactivity

Stability.....	Stable at normal temperatures and pressures.
Reactivity conditions.....	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Incompatibility.....	Keep away from heat. Incompatible with strong oxidizers. Metal hydrides, iron chlorides.
Hazardous products of decomposition.....	By fire: Dense black smoke. Oxides of carbon (CO,CO2). Styrene oxide. Hydrocarbons.
Hazardous polymerization.....	Hazardous polymerization will not occur.

PRODUCT: AV 7658 ROCKER PANEL PROTECTOR BLACK**Section 11: Toxicological information**

Ingredients	LC50	LD50
ACETIC ACID, TERT-BUTYL ESTER	>2,230 mg/m ³ 4 hours rat	4,100 mg/kg rat oral >2,000 mg/kg rabbit dermal
TOLUENE	8000 ppm rat inhalation	5,000 mg/kg rat oral; 12,124 mg/kg rabbit dermal
CALCIUM CARBONATE	No data	6450 mg/kg rat oral
PROPANE	>1,464 mg/L 15 minutes rat	No data
SBR (STYRENE BUTADIENE RUBBER)	No data	No data
ISOBUTANE	52 mg/L 1 hour mouse	No data
SOLVENT NAPHTHA, HEAVY ALIPHATIC	>6 mg/L 4 hours rat	>2,000 mg/kg oral rat >2,000 mg/kg dermal rabbit
BENTONE	No data	No data
CARBON BLACK	No data	>8,000 mg/kg oral (rat)
CRYSTALLINE SILICA	No data	No data
Route of entry	Eye contact. Skin contact. Inhalation.	
Effects of acute exposure.....	The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation.	
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Possible damage to liver and kidneys. May cause damage to the respiratory system, lungs, eyes, skin and central nervous system. Cardiac abnormalities and reproductive organ damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal .	
Skin contact.....	Can cause moderate irritation, defatting and dermatitis.	
Skin absorption.....	Chronic skin exposure to solvents may cause effects similar to those identified under chronic inhalation.	
Eye contact.....	Can cause redness, irritation, tissue destruction.	
Ingestion.....	Aspiration of material into lungs can cause chemical pneumonitis which can be fatal. May be harmful or fatal if swallowed.	
Carcinogenicity of material.....	This product contains Crystalline silica and Carbon Black that are known to the State of California to cause cancer.	
Reproductive effects.....	Toluene is known by the State of California to cause adverse fetal developmental effects.	
Toxicological Data		

Section 12: Ecological information

Environmental.....	Do not allow to enter waters, waste water or soil.
Biodegradability.....	No data.

Section 13: Disposal considerations

Waste disposal.....	Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty. This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.
---------------------	--

Section 14: Transport information

TDG Classification.....	UN1950 - AEROSOLS, flammable - Class 2.1 - This product meets limited quantity exemption when shipped in containers less than 1 Litre.
DOT Classification (Road).....	UN1950 - AEROSOLS, flammable - Class 2.1 - Ltd Qty (1 Liter/0.26 Gallons).
IATA Classification (Air).....	UN1950 - AEROSOLS, flammable - Class 2.1 - Limited Quantity.
IMDG Classification (Marine).....	UN1950 - AEROSOLS - Class 2.1 - EmS: F-D, S-U - Limited Quantity.
Marine Pollutant.....	Potential marine pollutant.
Proof of Classification.....	In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

Section 15: Regulatory information

WHMIS classification.....	A. B5. D2A. D2B.
CEPA status.....	On Domestic Substances List (DSL).
OSHA.....	This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III	

PRODUCT: AV 7658 ROCKER PANEL PROTECTOR BLACK**Section 15: Regulatory information**

Section 302 - extremely hazardous None.
 substances
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... Toluene.
 EPA hazardous air pollutants (HAPS) Toluene.
 40CFR63
 TSCA inventory status..... All components are listed.
 California Proposition 65..... This product contains Crystalline silica and Carbon Black that are known to the State of California to cause cancer. This product contains Toluene known to the State of California to cause (developmental) reproductive toxicity.

Section 16: Other information

Prepared by: REGULATORY AFFAIRS.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Preparation date: Mar12/15